



PRO 275

Updated: Apr. 9th, 2024 - [Changes are in blue text](#)

Any questions or concerns, please email chrispask@milandragway.com

General Class Requirements:

- Any Transmission
- Dual Power Adders are Prohibited
- (Except Diesel Entries)
- Tire - M/T Pro 275 only
- Any Suspension
- No Wheelie Bars
- Generally Shaped Cars & Body
- (New designed bodies are required to send images in for approval to mail@radialoutlaws.com)
- No Pro Mods
- OEM Style Fiberglass Body is Accepted
- Stock Wheelbase +/- 2 inches
- Front Overhang Maximum of 45 inches from center of spindle

-
- (+50 lbs. to any combo with more than 3 forward gears,
 - Except Nitrous & Turbo Entries)

- BB NOS 5.0 - 2300
- BB NOS over 5.0 - 2450 (905 & Smaller - 2400)

- Diesel - 2850

- SB SINGLE – 2325
- BB SINGLE – 2425
- SB TT 2425 (Up to 4.500 bore space, under 500 cu in)
- SB TT 2550 (4.600 bore space, or over 500 cu. in.)
- SB TT 2625 (Hemi)
- BB TT - 2700 (ANY SIZE TURBO)
- BB TT (Non-HEMI) - 2650 (ANY SIZE TURBO)



- SB PROCHARGER - 2400 (Stock Bore Space)
- SB PROCHARGER - 2500 (4.500 Bore Space)
- SB PROCHARGER - 2600 (4.600 Bore Space)
- SB PROCHARGER - (HEMI add 50lbs. to any Bore Space Weight)
- BB PROCHARGER - 2775 (Non-HEMI - 2600)
 - (-75 LBS VORTECH 131 MAX ONLY)
 - (-50 LBS for 526 cu in and under)

Centrifugal Supercharger

The maximum specification for the compressor wheel tip to tip is limited to 140.99mm inducer diameter. Measurement will be taken at the point where the leading edge of the compressor wheel meets the inlet housing. All air entering the Supercharger must pass through a single inlet opening. Exducer backing plate and blade tip to tip dimensions may not exceed 188.99

(No Centrifugal entry with any gear drive or blower that is not readily available for immediate sale & delivery at least 21 days before race)

(No test or prototype of any kind allowed)

- SB ROOTS - 2400
- BB ROOTS - 2650

- SB SCREW - 2575 (Stock Bore Space)
- SB SCREW - 2625 (4.500 Bore Space)
- SB SCREW - 2675 (4.600 Bore Space)
- SB SCREW - (HEMI add 50lbs. to any Bore Space Weight)
- BB SCREW 92 OVER – 2775 (Non- Hemi 2725)
- BB SCREW – 2900 (Non- Hemi 2785)

- BB TWIN PROCHARGER - 2675
- 4 cyl. / 6 cyl. Combo - 2475 (production engines only)
- (-150 LBS any cast block cast head combo)
- (-75 LBS for Cast Heads)